



**NTN UCFLU-1.5/8 Flange Block Bearings**



Bearing No. UCFLU-1.5/8

UCFLU-1.5/8 Bearing 2D drawings and 3D CAD models

Category	Flange Block Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight	8.51
EAN	4547359214772
Product Group	M06110
Number of Mounting Holes	2
Mounting Method	Set Screw
Housing Style	2 Bolt Flange Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	33/64 Inch
Relubricatable	Yes
Insert Part Number	A-UC208-110D1
Seals	Single Lip Land Riding
Housing Configuration	1 Piece Solid
Pilot Configuration	No Pilot
Inch - Metric	Inch
Long Description	2 Bolt Flange Block; 1-5/8" Bore; 5.8" Bolt Circle; 5-27/32" Bolt Spacing; 1 Piece Solid; Set Screw Mount; Cast Iron; Ball Bearing; 1-15/16" Length Thru Bore; Relubricatable; Singl



## Shanghai Sunpace Machinery Co., Ltd.

Other Features	Single Row   Wide Inner Race   Has Flinger
Category	Flange Block
UNSPSC	31171501
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Flanged
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
Manufacturer Item Number	UCFLU-1.5/8
Weight / LBS	18.75
Cartridge Pilot Depth	0 Inch   0 Millimeter
d	1.625 Inch   41.275 Millimeter
Nominal Bolt Circle Diameter Round	5.8 Inch   148 Millimeter
Cartridge Pilot Diameter	0 Inch   0 Millimeter
D	1.937 Inch   49.2 Millimeter
Bolt Spacing	5.844 Inch   148.438 Millimeter
bore diameter:	1.6250 in
seal type:	Contact with Flinger
bolt center-to-center length:	5.8438 in
length through bore:	2-9/64 in
overall length/diameter:	7.0938 in
finish/coating:	Uncoated
bore type:	Round
lubrication type:	Lubrication Fitting
duty type:	Standard Duty
series:	UCFLU
mounting type:	Two-Bolt Flange
standards met:	ISO, AFBMA
housing material:	Cast Iron
replacement bearing:	A-UC208-110D1



## Shanghai Sunpace Machinery Co., Ltd.

locking device:	Set Screw
manufacturer catalog number:	A-1400-V
expansion type:	Non-Expansion Bearing (Fixed)
manufacturer product page:	<a href="#">Click here</a>